



ORIENT BLACK® N134

FURNACE BLACK

PRODUCT DESCRIPTION

Orient Black N134 is a Super Abrasion Furnace grade (SAF) having high surface area and high structure, engineered to provide a high level of rubber reinforcement.

APPLICATION


Orient Black N134 provides superior abrasion resistance and durability in premium truck tyre, bus tyre, off the road (OTR) tyre and high performance tyre tread applications.







RECOMMENDED APPLICATION







High Performance Tread

Truck Tyre Tread

Passenger Car Tread

Inner Liner & Tubes

Profiles

Moldings

Hoses & Hose Covers Carcass

Wire Coat

Belting

QUALITY PARAMETERS

| Property | Unit | Typical value | Test method |
|-----------------------|------------------|----------------------|-------------------|
| STSA | m²/g | 137 | ASTM D6556 |
| lodine Adsorption No. | g/kg | 142 | ASTM D1510 |
| OAN | cm³/100g | 127 | ASTM D2414 |
| COAN | cm³/100g | 103 | ASTM D3493 |
| Tint Strength | Tint Unit | 131 | ASTM D3265 |
| Ash Content | % | ≤0.75 | ASTM D1506 |
| Heating Loss | % | ≤2.5 | ASTM D1509 |

PACKAGING

| Packaging mode | Per unit qty. (kg) | No. of bags/40 ft. container |
|----------------|--------------------|------------------------------|
| Paper Bag | 25 | 880 |
| Big Bag (FIBC) | 900 | 22 |

PRODUCT SAFETY

- Product is REACH registered
- · Refer to SDS for handling purpose

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | F: +91 33 2248 0140/2243 6681 | W: www.pcblltd.com
E: pcbl.mktg-international@rpsg.in | pcbl.mktg-national@rpsg.in | pcbl.rubbertech@rpsg.in







