

ORIENT BLACK[®] N774

FURNACE BLACK

PRODUCT DESCRIPTION

Orient Black N774 is a low surface area, low structure, semi-reinforcing furnace grade providing high resilience, good elasticity resistance and bending resistance.


APPLICATION

Orient Black N774 can be used as reinforcing filler for belting, moldings, hoses, hose cover, tyre inner liner, tubes and profile. It gives excellent processibility in numerous rubber goods.



RECOMMENDED APPLICATION

 Highly recommended  Recommended under advice  Not recommended



QUALITY PARAMETERS

Property	Unit	Typical value	Test method
STSA	m ² /g	30	ASTM D6556
Iodine Adsorption No.	g/kg	29	ASTM D1510
OAN	cm ³ /100g	72	ASTM D2414
COAN	cm ³ /100g	63	ASTM D3493
Ash Content	%	≤0.75	ASTM D1506
Heating Loss	%	≤1.5	ASTM D1509

PACKAGING

Packaging mode	Per unit qty. (kg)	No. of bags/40 ft. container
Paper Bag	25	960
Big Bag (FIBC)	1150	20

PRODUCT SAFETY

- Product is REACH registered
- Refer to SDS for handling purpose

PCBL Limited

Registered Office: 31 Netaji Subhas Road, Kolkata - 700 001, WB, India
Corporate Office: RPSG House, 4th Floor, 2/4 Judges Court Road, Kolkata - 700 027, WB, India
P: +91 33 6625 1443 | **F:** +91 33 2248 0140/2243 6681 | **W:** www.pcbltd.com
E: pcbl.mktg-international@rpsg.in | pcbl.mktg-national@rpsg.in | pcbl.rubbertech@rpsg.in

